

CONTACT US

www.unitedtelsupply.com

rotect Your Fiberglass Posts

TEL · SUPPLY

Traditional fiberglass posts get fuzzy over time when the damaging effects of UV light cause the surface resin of the post to evaporate. Without the surface resin, the glass fibers become exposed, not only causing significant fading, but posts in this condition can be a safety hazard to any person or animal that may come into contact with it.



Our patented PolyTech Coating[™] blocks damaging UV rays, prevents fiberbloom, and is available on all of our Fiberglass Composite posts. Images to the right are after 2,000 hours of Weatherometer testing.



Without PolyTech Coating



f (**o**) in

With PolyTech Coating



RI

Rhino 3-Rail[®] Fiberglass

Rhino's 3-Rail fiberglass composite post uses the industry standard profile. It's our most drivable fiberglass marker and can be installed in almost any soil condition. The design allows for easy stacking and storing and has the durability to withstand repeated impacts when hit from the front or back.



DESCRIPTION:

- Standard Lengths: 62" | 66" | 72"
- Width: 4"
- · Pultruded fiberglass set in a composite resin
- · Side-rails and reinforcing rib provide strength and rigidity
- Temperature stable

S O L U T I O N S™

- Fire resistant
- · Pointed end for easy installation
- · 10-year warranty for posts that include our patented PolyTech Coating™

- · Can withstand direct impacts and return to standing position
- Decals can be applied to front and back *Decals sold separately



Options & Accessories: Page 12









Rhino 4-Rail[™] Fiberglass

The Rhino 4-Rail[™] is the industry's second most popular profile topped only by our 3-Rail Fiberglass Post. It's design allows the post to bend over when hit, then snap back into its normal upright position.

DESCRIPTION:

- Standard lengths: 62" | 66" | 72"
- Width: 4"
- Pultruded fiberglass set in a composite resin
- · Side-rails and reinforcing rib provide strength and rigidity
- Temperature stable
- Fire resistant
- · Pointed end for easy installation
- · 10-year warranty for posts that include our patented PolyTech Coating™
- · Can withstand direct impacts and return to standing position
- Decals can be applied to front and back *Decals sold separately

STANDARD POST COLOR



ALTERNATIVE POST COLORS





Options & Accessories: Page 12

Steel U-Channel Post

1.12 lb. U-channel posts are ideal for mounting utility warning signs, TriView Sleeves™ or TriView Extensions™. 2 lb. posts are designed to support aerial marker frames and larger signs.

DESCRIPTION:

- · Corrosion resistant metal
- 3/8" holes 1" on center

1.12LB. OPTIONS:

- Standard Coating: Green
- · Alternative Coatings: Yellow, White, Orange, Galvanized
- · Standard length: 6'
- Alternative lengths available upon request

2LB. OPTIONS:

- Standard Coating: Galvanized
- · Alternative Coatings: Yellow, White, Orange, Green
- · Standard length: 6'
- Alternative lengths available upon request

Options & Accessories: Page 12