

MEGA TITAN-48 UPS



MEGA TITAN-48V

Introducing the Mega Titan 48V UPS! Designed for outdoor or indoor deployments for MDU or business ONTs. The Mega TITAN provides a continuous –48V of UPS power including ONT alarms placed on a CAT-5 connection for easy field termination. Our field proven battery management system ensures long life and reliable power in harsh environments.

- · -48V @ 150W
- 10 Year design-life GS Battery.
- 10 to 12-hour runtime with typical 150W rated ONTs.
- Automatic 45-day battery testing.
- Temp compensated battery charging.
- Steel enclosure built by SPC
- Designed and Manufactured in the USA!





MEGA TITAN-48 Outdoor UPS Specifications

Input AC Input Voltage AC Input Frequency Plug Type Cable Lenth

90V - 305Vac 47/63 Hz 3 prong grounded 12'

DC Output Power

Voltage Connector Alarms 150 watts 45V - 50V 2 position screw terminal Battery On Battery Low Battery Fail Battery Missing

GS Battery PYL12V80TT

Lead acid

80Ah

Battery

Type Model Capacity

Physical Dimensions Weight Power Cable Alarms Mounting Options

16"H x 12"W x 8"D (in./approx) 75 lbs. 12AWG Cat-5 connection Wall or pole mount

-40°C to +55°C (-40°F to + 131°F)

0% to 95% non condensing

FCC 47 CFR Part 15 Class B

Environment

Operating Temperature Operating Humidity

Safety Compliance Specification:


Emissions:

Warranty

5 years

EN-60950-1 EN-60950-2





Bold indicates industry-best



Specifications subject to change without notice

630 Lincoln Ave., Clay Center, KS 67432 • 877-799-3774 • www.espicorp.com

© 2017 ESPi. All Rights Reserved. All trademarks mentioned are property of their owners.