

RACK MOUNT MEGA TITAN-48UPS



Introducing the Mega Titan 48V UPS! Designed for outdoor or indoor deployments for MDU or business ONTs. The Mega TITAN provides a continuous –48V of UPS power including ONT alarms placed on a CAT-5 connection for easy field termination. Our field proven battery management system ensures long life and reliable power in harsh environments.

- •-48V @ 150W
- •10 Year design-life GS Battery.
- •10 to 12-hour runtime with typical 150W rated ONTs.
- Automatic 45-day battery testing.
- •Temp compensated battery charging.
- •2 RU space requirement
- •Designed and Manufactured in the USA!





RACK MOUNT MEGA TITAN-48



Input

AC Input Voltage 90V - 305Vac
AC Input Frequency 47/63 Hz
Plug Type 3 prong grounded

Cable Length 1

DC Output

Power 150 watts Voltage 48V

Connector 2 position screw terminal
Alarms On Battery, Battery Low
Battery Fail, Battery Missing

Battery

Type Lead acid

Model GS Battery PYL12V80TT

Capacity 80A

Physical

2 RU

Dimensions 3.5" H x 19"W x 11.5"D (in./approx)

Weight 10lbs. (without Battery)

Power Cable 12AWG

Alarms Cat-5 connection

Mounting Options 19" Rack

Environment

Operating Temperature -40°C to +55°C (-40°F to +131°F)
Operating Humidity 0% to 95% non condensing

Safety Compliance

Emissions: FCC 47 CFR Part 15 Class B

Warranty 5 years

Bold indicates industry-best



Specifications subject to change without notice