


Category 5e

CMR/CMX Outdoor



SPECIFICATIONS

| | |
|-----------------------------------|--|
| Pair Count | 4 |
| Conductor | Solid annealed copper |
| AWG (mm) | 24 (0.51) |
| Insulation | Polyolefin |
| Insulation Colors | Pair 1: ColorTip Light Blue, Blue Pair 2: ColorTip Light Orange, Orange Pair 3: ColorTip Light Green, Green Pair 4: ColorTip Light Brown, Brown |
| Ripcord | Non-wicking polyester yarn |
| Jacket | Tough, flame retardant, weather and abrasion resistant PVC |
| Characteristic Impedance Ohms | 100 ± 15 |
| Nominal Velocity of Propagation % | 70 |
| Performance Compliance | UL 444 CSA C22.2 No. 214-08 UL 1581 UL 1666 ANSI/TIA-568-C.2 ANSI/ICEA S-90-661-2012 ANSI/TIA/EIA-570-B Article 800, NEC (NFPA 70) RoHS-compliant/RoHS 2-compliant |
| NRTL Programs | UL, c(UL) Listed CMR UL, c(UL) Listed CMX Outdoor |

ENVIRONMENTAL SPECIFICATIONS AND TESTS

| | |
|---|--|
| Operation | -40°F to +167°F (-40°C to +75°C) |
| Installation | -40°F to +140°F (-40°C to +60°C) |
| ANSI/ICEA 5-100-685-2009 Tested down to -67°F (-55°C) | Section 7.1: -4°F (-20°C) cold bend test Section 7.2: +14°F (-10°C) cold impact test Section 7.3: -40°F (-40°C) anvil test |

PART NUMBERS AND PHYSICAL CHARACTERISTICS

| Part Number ¹ | Nominal Diameter in (mm) | Approx. Weight lbs/kft (kg/km) | Package | Packages per Pallet |
|--------------------------|--------------------------|--------------------------------|-----------------|---------------------|
| 51-240-x1 | 0.21 (5.3) | 21 (31) | 1,000' POP™ box | 36 |

JACKET COLORS

| | | | | |
|--------------------------------|-----------|----------|----------|-----------|
| ¹ Replace "x" with: | Beige = 1 | Blue = 2 | Gray = 3 | White = 4 |
|--------------------------------|-----------|----------|----------|-----------|

UL is a registered trademark of UL LLC.

PRODUCT DESCRIPTION

The Superior Essex Category 5e CMR/CMX Outdoor cable is specifically designed for outdoor applications. UV-blocking compounds aid in protecting the cable from light. Applications include Ethernet interconnect cable for Wi-Fi or retrofit cable installations that employ exterior runs having long-term outdoor exposure between two environmentally protected points. CMX Outdoor cables are designed to extend the run between the Network Interface Unit and the point of entry into the interior of a residence or a premise.

Superior Essex CAT 5e CMR/CMX Outdoor premises cable has been tested and listed as UL® 444 Outdoor compliant. This designation requires the cable to resist 300 hours of UV and heat. In addition, the CMR listing allows the cable to be used in riser spaces per UL 1666, eliminating the need to transition to fire resistant cables.

APPLICATIONS

- 10BASE-T through 1000BASE-T Ethernet
- Power over Ethernet (PoE) - IEEE 802.3af
- PoE+ - IEEE 802.3at Type 1 and 2
- ATM and token ring

FEATURES

- Tough, weather resistant PVC jacket
- Combined indoor/outdoor rating
- Meets ANSI/TIA-568-C.2 specification
- Moisture-resistant package
- CableID® alpha numeric code printed every 2 feet
- QuickCount® marking system in feet and meters
- ColorTip® Circuit Identification System

BENEFITS

- Increases life of cable by providing low temperature handling and UV resistance; cable jacket resists cracking over time
- Reduces inventory by eliminating multiple cable types
- CAT 5e compliance
- Resists damp conditions that might weaken standard packages
- Allows both ends of a cable run to be easily identifiable without the need to separately label or tone the cable
- Provides remaining length of cable on reel
- Easily identifiable conductor mates even in low light environments



CAUTIONARY INFORMATION

- Do not use as a substitute for Outside Plant (OSP) cables.
- Do not use in conduit or direct burial which can flood. These cables are not designed for extended exposure to water.

