

# GOPIC®-F

RDUP PE-39



## SPECIFICATIONS

<b>Conductor</b>	Solid annealed copper
<b>Insulation</b>	Solid polyolefin; color coded in accordance with industry standards
<b>Twisted Pairs</b>	Individual insulated conductors; twisted into pairs with varying lay lengths; specific color combinations provide pair identification
<b>≤ 25-Pair Core</b>	Pairs are assembled into a cylindrical core
<b>&gt; 25-Pair Core</b>	Cables larger than 25-pair are assembled into units, which are then used to assemble the core; units are identifiable using color-coded binders
<b>Filling Compound</b>	80°C ETPR compound, completely filling the interstices between the pairs and under the core wrap
<b>Core Wrap</b>	Non-hygroscopic, dielectric tape applied over the core
<b>Shield</b>	Corrugated, rodent resistant, copper bearing armor applied longitudinally with an overlap; flooded shield interfaces
<b>Jacket</b>	Black, polyethylene
<b>Jacket Marking</b>	Identifying information includes a telephone handset, cable code, pair count, AWG, date of manufacture and sequential length markings at 2 foot intervals
<b>Standards Compliance</b>	ANSI/ICEA S-84-608-2011 RDUP 7 CFR 1755.390 (PE-39) RoHS-compliant

## PRODUCT DESCRIPTION

GOPIC®-F Cables are designed for use in direct burial applications where additional mechanical or rodent protection is required. GOPIC-F may be used aerially, but must be attached to a support strand.

## APPLICATIONS

- Direct burial where additional mechanical protection is required or desired
- Lashed aerial where additional mechanical protection is required or desired

## FEATURES

- Twisted into pairs with varying lay lengths
- Core wrap
- Filled core
- Corrugated, copper bearing armor
- Fully flooded shield interfaces
- Black, polyethylene jacket

## BENEFITS

- Minimizes crosstalk
- Provides thermal protection
- Moisture resistant
- Rodent resistant
- Inhibits corrosion and water migration
- Provides a tough, protective covering designed to withstand exposure to direct sunlight, atmospheric temperature changes and stresses expected in standard installations

## ELECTRICAL SPECIFICATIONS

Number of Pairs	Average Mutual Capacitance @ 1,000 Hz nF/mile (nF/km)	Capacitance Unbalance Pair to Pair @ 1 kHz		Capacitance Unbalance Pair to Ground @ 1 kHz	
		Maximum Individual pF @ 1 kft (pF @ 1 km)	Maximum RMS pF @ 1 kft (pF @ 1 km)	Maximum Individual pF @ 1 kft (pF @ 1 km)	Maximum Average pF @ 1 kft (pF @ 1 km)
12 or less	83 ± 7 (52 ± 4)	80 (145)	-	800 (2,625)	-
Over 12	83 ± 4 (52 ± 2)	80 (145)	25 (45)	800 (2,625)	175 (574)

Conductor Size AWG (mm)	Minimum Insulation Resistance @ 68°F (20°C) gigohm-mile (gigohm-km)	Maximum Average Attenuation* 772 kHz @ 68°F (20°C) dB/kft (dB/km)	Maximum Conductor Resistance @ 68°F (20°C) Ohms/sheath mile (km)	DC Resistance Unbalance Maximum %		Dielectric Strength DC Potential - Volts	
				Average	Individual Pair	Conductor to Conductor	Conductor to Shield
19 (0.90)	1.0 (1.6)	2.8 (9.2)	45.0 (28.0)	1.5	5.0	7,000	15,000
22 (0.64)	1.0 (1.6)	4.0 (13.1)	91.0 (56.5)	1.5	5.0	5,000	15,000
24 (0.51)	1.0 (1.6)	5.0 (16.4)	144.0 (89.5)	1.5	5.0	4,000	15,000

\*For cables of 12-pair or less, the maximum average attenuation may be increased by 10% over the values shown.

### Minimum Near End Crosstalk (NEXT) @ 772 kHz

PSWUNEXT Mean (dB)	47
PSWUNEXT Worst Pair (dB)	42

### Minimum Far End Crosstalk (FEXT) @ 772 kHz

Conductor Size (AWG)	19	22	24
PSELFEXT Mean (dB/kft)	51	49	49
PSELFEXT Worst Pair (dB/kft)	45	43	43

CONTACT US



1841 Industrial Ave  
San Angelo, TX 76904  
(325) 262-4031

www.unitedtelsupply.com



and



## PART NUMBERS AND PHYSICAL CHARACTERISTICS

Part Number	Pair Count	AWG (mm)	Nominal Diameter in (mm)	Approx. Weight lbs/kft (kg/km)	Standard Length ft (m)	Approx. Shipping Weight lbs (kg)	Reel Size F x T x D in
04-026-27	6	19 (0.90)	0.54 (14)	155 (230)	5,000 (1,524)	885 (400)	44 x 18 x 20
04-028-27	12	19 (0.90)	0.69 (18)	255 (380)	5,000 (1,524)	1,440 (655)	46 x 25 x 20
04-031-27	25	19 (0.90)	0.92 (23)	470 (700)	5,000 (1,524)	2,720 (1,235)	65 x 30 x 32
04-034-27	50	19 (0.90)	1.22 (31)	850 (1,265)	5,000 (1,524)	4,950 (2,245)	78 x 40 x 39
04-038-27	100	19 (0.90)	1.69 (43)	1,620 (2,410)	2,500 (762)	4,665 (2,115)	72 x 35 x 36
04-057-27	6	22 (0.64)	0.43 (11)	95 (140)	5,000 (1,524)	540 (245)	36 x 18 x 14
04-059-27	12	22 (0.64)	0.53 (14)	150 (225)	5,000 (1,524)	860 (390)	44 x 18 x 20
04-062-27	25	22 (0.64)	0.68 (17)	260 (385)	5,000 (1,524)	1,465 (665)	46 x 25 x 20
04-065-27	50	22 (0.64)	0.89 (23)	450 (670)	5,000 (1,524)	2,495 (1,130)	58 x 25 x 20
04-069-27	100	22 (0.64)	1.19 (30)	820 (1,220)	5,000 (1,524)	4,715 (2,140)	72 x 35 x 36
04-073-27	200	22 (0.64)	1.63 (41)	1,555 (2,315)	2,500 (762)	4,500 (2,040)	72 x 35 x 36
04-075-27	300	22 (0.64)	1.96 (50)	2,275 (3,385)	2,500 (762)	6,385 (2,895)	78 x 40 x 39
04-092-27	6	24 (0.51)	0.38 (9.7)	70 (105)	5,000 (1,524)	415 (190)	36 x 18 x 14
04-094-27	12	24 (0.51)	0.46 (12)	110 (165)	5,000 (1,524)	660 (300)	44 x 18 x 20
04-097-27	25	24 (0.51)	0.58 (15)	180 (270)	5,000 (1,524)	1,065 (485)	46 x 25 x 20
04-100-27	50	24 (0.51)	0.74 (19)	310 (460)	5,000 (1,524)	1,755 (795)	52 x 25 x 20
04-104-27	100	24 (0.51)	0.98 (25)	550 (820)	5,000 (1,524)	3,120 (1,415)	65 x 30 x 32
04-108-27	200	24 (0.51)	1.32 (34)	1,020 (1,520)	5,000 (1,524)	5,800 (2,630)	78 x 40 x 39
04-110-27	300	24 (0.51)	1.58 (40)	1,475 (2,195)	2,500 (762)	4,300 (1,950)	72 x 35 x 36
04-112-27	400	24 (0.51)	1.79 (46)	1,910 (2,845)	2,500 (762)	5,475 (2,485)	78 x 40 x 39
04-116-27	600	24 (0.51)	2.18 (55)	2,825 (4,205)	1,250 (381)	4,145 (1,880)	72 x 35 x 36
04-118-27	900	24 (0.51)	2.63 (67)	4,145 (6,170)	1,250 (381)	5,880 (2,665)	78 x 40 x 39
04-120-27	1,200	24 (0.51)	3.00 (76)	5,435 (8,090)	1,000 (305)	6,135 (2,780)	78 x 40 x 39
04-124-27	1,800	24 (0.51)	3.63 (92)	8,005 (11,915)	1,000 (305)	9,180 (4,165)	96 x 40 x 48

**FOR EXTREME RISK ENVIRONMENTS**

For extreme direct burial or lashed aerial installations, this cable is available with the +M feature. See the "Mechanical Protection (+M) for Extreme Risk Environments" in the "Technical Information" section for more information.